

Standard Industrial pressure snubbers (NPT Threads)


1/8" NPT Male x 1/8" NPT Female					
Model No.	Material	Length	Hex	Net weight	Maximum Pressure Rating
12B	Brass	1.1"	5/8"	½ oz.	3,000 psi
12S	Stainless Steel (303)	1.1"	5/8"	½ oz.	5,000 psi
12S6	316 Stainless Steel	1.1"	5/8"	½ oz.	5,000 psi



¾" NPT Male x ¼" NPT Female					
Model No.	Material	Length	Hex	Net weight	Maximum Pressure Rating
25B	Brass	1.5"	3/4"	2 oz.	10,000 psi
25S	Stainless Steel (303)	1.5"	3/4"	2 oz.	15,000 psi
25S6	316 Stainless Steel	1.5"	3/4"	2 oz.	15,000 psi
25M	Monel	1.5"	3/4"	2 oz.	15,000 psi



½" NPT Mal	½" NPT Male x ½" NPT Female				
Model No.	Material	Length	Hex	Net weight	Maximum Pressure Rating
50B	Brass	2.2"	1¼"	8 oz.	10,000 psi
50S	Stainless Steel (303)	2.2"	1¼"	8 oz.	15,000 psi
50S6	316 Stainless Steel	2.2"	1¼"	8 oz.	15,000 psi
50M	Monel	2.2"	1¼"	8 oz.	15,000 psi



High Pressure 20,000 psi - Stainless Steel (Special)					
Model No.	Connections	Length	Hex	Net weight	Maximum Pressure Rating
2025	¼" NPT Male x ¼" NPT Female	2"	1¼"	??????	20,000 psi
2050	½" NPT Male x ½" NPT Female	2.5"	2"	12 oz.	20,000 psi

Add suffix to model no. to Indicate desired porosity (e.g. 12BE)

	Porosity	Approx. micron rating
С	Highly Viscos Fluids (over 500 S.S.U.)	75
D	Oil (225 S.S.U. to 500 S.S.U.	40-45
E	Water & Light Oils (30 to 225 S.S.U.)	10
F	Vapor and Low Viscosity Fluids (under 30 S.S.U.)	7
G	Air or other Gases	2-5
HX	Pulsating Gas	1
HXX	Extreme Gas Pulsation	1/2
Р	Special porosity Special discs to repel water or smaller micron ratings	

	Other Threaded Connections	
BSPP	British Pipe thread parallel (Example: 25B-BSPP)	
BSPT	British Pipe thread taper (Example: 25B-BSPT)	
NPS	NPS (Example: 25B-NPS)	
	Metric	


	Options		
	(Special) Monel porous disc (With monel housing)		
	Cleaned for oxygen service		
LF	Lead free		

Special NPT pressure Snubbers

Chemiquip Snubbers Are available in any configuration use these numbers by ordering

- 1. Select configuration
- 2. Select material
- 3. Select porosity


Model No.	Configuration
40	%" NPT Male x %" NPT Female
75	¾" NPT Male x ¾" NPT Female
1M2	1/4" NPT Male x 1/4" NPT Female
5M2	½" NPT Male x ¼" NPT Female
2M5	¼" NPT Male x ½" NPT Female
90	Other configurations Male x Female



High Pressu	High Pressure 20,000psi		
2025	¼" NPT Male x ¼" NPT Female		
2050	½" NPT Male x ½" NPT Female		

Male x Male		
25MXM	¼" NPT Male x ¼" NPT Male	
50MXM	½" NPT Male x ½" NPT Male	
90MXM	Other configurations Male x Male	

Female x Fe	Female x Female		
F25	¼" NPT Female x ¼" NPT Female		
F50	½" NPT Female x ½" NPT Female		
F90	Other configurations Female x Female		



2.	Material
В	Brass
S	Stainless Steel (303)
S6	316 Stainless Steel
M	Monel
Z	Other (Please Specify)

Add suffix to model no. to Indicate desired porosity (e.g. 40BE)


3.	Porosity	Approx. micron rating
С	Highly Viscos Fluids (over 500 S.S.U.)	75
D	Oil (225 S.S.U. to 500 S.S.U.	40-45
E	Water & Light Oils (30 to 225 S.S.U.)	10
F	Vapor and Low Viscosity Fluids (under 30 S.S.U.)	7
G	Air or other Gases	2-5
HX	Pulsating Gas	1
HXX	Extreme Gas Pulsation	1/2
Р	Special porosity Special discs to repel water or smaller micron ratings	

2 2	at. No. Ho M5B Bi M5S St M5M M

	Other Threaded Connections				
BSPP	British Pipe thread parallel (Example: 40B-BSPP)				
BSPT	British Pipe thread taper (Example: 40B-BSPT)				
NPS	NPS (Example: 40B-NPS)				
	Metric				

NPT x Flared Tubing Connections Pressure snubbers

	Coupling Flared x NPT (Stainless Steel)								
Model No.	Tubing (O.D)	NPT Pipe	Length	Hex?	Net weight	Maximum Pressure Rating?			
12-FR-4	1/4"	⅓" Female	1.3/16"		1 oz.				
12-FR-5	5/16"	⅓" Female	1 3/16"		1 oz.				
25-FR-4	1/4"	¼" Female	1 3/8"		1 oz.				
25-FR-5	5/16"	¼" Female	1 7/16"		1 oz.				
25-FR-6	3/8"	¼" Female	1 7/16"		1 oz.				
12-MR-4	1/4"	⅓" Male	11/8"	1/2"?	?????				
12-MR-5	5/16"	⅓" Male	1 3/16"		2 oz.				
25-MR-4	1/4"	¼" Male	1 3/8"		?????				
25-MR-5	5/16"	¼" Male	1 5/16"		2 oz.				
25-MR-6	3/8"	¼" Male	1 7/16"		?????				
50-MR-4	1/4"	½" Male	??????		3 oz.				
50-MR-5	5/16"	½" Male	??????		3 oz.				
50-MR-6	3/8"	½" Male	??????		3 oz.				



Standard Materials of construction: ????

Housing:

- 303 Stainless Steel
- 316 Stainless Steel
- (Cadium plated carbon steel?)
- Aluminum
- Monel

